



**12 YEARS**  
Guarantee on product  
material and workmanship


**25 YEARS**  
Linear Power output  
warranty

**STC irradiance**  
STC irradiance 1000W/m<sup>2</sup>  
Cell Temperature 25°C AM=1.5

**NOCT irradiance**  
NOCT irradiance 800W/m<sup>2</sup>  
Ambient Temperature 20°C AM=1.5



## Additional Value



## MECHANICAL CHARACTERISTICS

Cell Type	166x55.33Mono
No. of Cells	36(3x12)
Dimensions	740*540*25mm
Weight	4.2kg
Front Glass	3.2mm high transmission low iron,tempered glass
Frame	Anodized Aluminium Alloy
Junction box	IP65/IP67
Output cables	2.5mm <sup>2</sup> cable 50cm+mc4
MaxWind Load/Snow Load	2400Pa/5400Pa

## ELECTRICAL DATA(STC)

Model Type	FG 70M-36	FG 75M-36
Peak Power(Pmax)	70W	75W
Maximum Power Voltage(Vmp)	19.85	20.55
Maximum Power Current(Imp)	3.53	3.65
Open Circuit Voltage(Voc)	23.44	23.82
Short Circuit Current(Isc)	3.73	3.85
Module Efficiency(%)	17.52	18.77

\* STC: irradiance 1000 W/m<sup>2</sup>, AM 1.5G, and cell temperature of 25°C

## TEMPERATURE&MAXIMUM RATING

Maximum System Voltage(V)	1000
Maximum Series Fuse Rating(A)	10
Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.350%
Voc Temperature Coefficients(V/°C)	-0.270%
Isc Temperature Coefficients(A/°C)	+0.048%
NOCT Nominal Operating Cell Temperature( °C)	45±2
Operating and Storage Temperature( °C)	-40 ~ +85

## PACKING WAY

20FT	14Packages/1960PCS
40HQ	16Packages/4800PCS

## Future Green Technology Co., Ltd.

No.26 Longjing west road, Baiyun District, Guangzhou city, Guangdong Province, China.  
Email: info@futuregreenbattery.com Tel: +86-020-31230665

